

# Canon

 Color  
imageRUNNER  
C2620 / C3220



CORPORATE  
SYSTEMS



meap  
POWERED BY


## The Brilliance of Color and the Power of Customization.

The Color imageRUNNER® C2620/C3220 devices bring the power of high-quality, high-speed color to your enterprise so you can add value to all forms of communication. These systems utilize four-drum, single-pass engine technology to drive speeds of up to 26 ppm and 32 ppm, respectively, for both color and black-and-white output, along with Canon's industry-renowned imaging technology for the most faithful reproduction of text and images.

Incorporating Canon's MEAP® (Multifunctional Embedded Application Platform) development architecture, the Color imageRUNNER C2620/C3220 devices offer the unique ability to embed diverse and customizable applications that integrate into every aspect of your business workflow. Add to that a complete suite of color multifunctional capabilities to brilliantly distinguish your business from the rest.

### Color imageRUNNER C2620/C3220 Specifications

Technology:	Laser Electrostatic Transfer System	Network Interface:	10/100Base-T (RJ-45)	<b>Finisher-M1 (Optional)**</b>	
Developing System:	Dry Dual Component Developing System	Optional Send Functions		Number of Trays:	One
Acceptable Originals:	Sheets, Books, 3-Dimensional Objects (Up to 4.4 lb./2kg)	Sending Methods:	E-mail, I-Fax, Super G3 Fax (Optional), File Server (IPX, FTP, SMB), Mail Box	Tray Capacity	No Collating, Collate, and Group Mode:
Max. Original Size:	11" x 17" (Ledger)	Address Book Capacity:	1,800		1,000 Sheets (Statement-R, Letter-R, Letter)
Copy/Print Sizes		File Format:	B/W: TIFF, MTIFF, PDF Color: JPEG, PDF, PDF (Compact)		500 Sheets/30 Sets (Legal, 11" x 17", 12" x 18")
Cassette-Feeding:	Executive, Statement-R, Letter-R, Letter, Legal, 11" x 17", 12" x 18" Letter	Sending Sizes:	Statement to 11" x 17"	Staple Mode (Corner):	30 Sets (Letter-R, Letter, Legal, 11" x 17")
Optional Paper Deck:		Power Source:	120V AC, 60Hz, 15A	Max. Stapling Capacity:	30 Sheets (Letter-R, Letter)
Stack Bypass:	3-5/16" x 5-7/8" to 12-5/8" x 18" (100mm x 148mm to 320mm x 457mm)	Dimensions (H x W x D) (Printer and Reader):	31-1/2" x 24-3/8" x 31" (799mm x 620mm x 786mm)		20 Sheets (Legal)
Magnification		Weight (Printer and Reader):	Approximately 277 lb. (126kg)	Acceptable Paper Weights:	17 lb. Bond to 140 lb. Index
Standard Mode:	100%	<b>Accessories</b>		Power Source:	From the Cassette Feeding Unit-X1 or Plain Pedestal-C1
Preset Reduction:	25%, 50%, 64%, 73%, 78%	<b>Duplexing Automatic Document Feeder-K1*</b>		Dimensions (H x W x D):	14-1/4" x 21-3/4" x 22-5/8" (362mm x 553mm x 574mm)
Preset Enlargement:	121%, 129%, 200%, 400%	Acceptable Originals:	Statement to 11" x 17"	Weight:	39.6 lb. (18kg)
Zoom Mode:	25% - 400% (in 1% Increments)	Acceptable Paper Weights:	14 lb. to 28 lb. Bond (52gsm to 105gsm)	<b>Finisher-N1** and Saddle Finisher-N2 (Optional)**</b>	
Copy/Print Speeds (Letter)		Tray Capacity:	Statement-R, Letter-R, Letter (30 Sheets/20 lb. Bond), Legal, 11" x 17" (15 Sheets/20 lb. Bond)	Number of Trays:	Two
C2620:	26 ppm (Color and B/W)	Power Source:	From Main Unit	Tray Capacity	No Collating, Collate, and Group Mode:
C3220:	32 ppm (Color and B/W)	Dimensions (H x W x D):	6-1/2" x 22-7/8" x 19-7/8" (165mm x 580mm x 506mm)		1,000 Sheets (Statement-R, Letter)
First-Copy Time:	13.1 Seconds (Color)	Weight:	28.6 lb. (13kg)	Staple Mode:	300 Sheets (Mixed Sizes)
Warm-Up Time:	9.8 Seconds (B/W)	Scanning Speed (LTR):	36 ipm (B/W); 36 ipm (Color, 300 dpi or Less); 23 ipm (Color, Greater Than 300 dpi)		750 Sheets/30 Sets (Letter)
	6 Minutes Max. After Powering On (68°F/20°C)	<b>Cassette Feeding Unit-X1 (Optional)</b>		Max. Stapling Capacity:	50 Sheets (Letter)
	6 Minutes From Sleep Mode (Approx.) 30 Seconds From Low-power Mode	Paper Capacity:	Dual 550-Sheet Paper Cassettes (1,100 Sheets/20 lb. Bond)	Acceptable Paper Weights:	30 Sheets (Letter-R, Legal, 11" x 17"; 17 lb. to 20 lb. Bond)
Image Server Memory:	1GB	Acceptable Paper Sizes:	Executive, Statement-R, Letter-R, Letter, Legal, 11" x 17", 12" x 18"	Available Staple Size	Letter-R, Letter, Legal, 11" x 17"
Resolution		Acceptable Paper Weights:	17 lb. Bond to 110 lb. Index	Corner Stapling:	Letter-R, Letter, Legal, 11" x 17"
Scanning:	600 x 600 dpi	Power Source:	120V AC, 60Hz, 15A	Double Stapling:	Letter, 11" x 17"
Printing:	Up to 2400-dpi Equivalent x 600 dpi	Dimensions (H x W x D):	12-1/4" x 24-3/8" x 27-3/4" (312mm x 620mm x 705mm)	Saddle-Stitching	
Halftone:	256 Gradations	Weight:	67.3 lb. (30kg)	Acceptable Paper Sizes:	Letter-R, 11" x 17"
Copy Exposure:	Automatic or Manual (9 Levels)	<b>Plain Pedestal-C1 (Optional)</b>		Tray Capacity:	1 to 5 Sheets: 25 Sets 6 to 10 Sheets: 15 Sets 11 to 15 Sheets: 10 Sets
Paper-Feeding Standard:	Dual 550-Sheet Paper Cassettes (1,100 Sheets; 20 lb. Bond/80gsm) Stack Bypass (100 Sheets; 20 lb. Bond)	Power Source:	120V AC, 60Hz, 15A	Max. Stapling Capacity/Set:	15 Sheets
Optional:	Dual 550-Sheet Paper Cassettes (1,100 Sheets; 20 lb. Bond) Paper Deck (2,700 Sheets; 20 lb. Bond)	Dimensions (H x W x D):	12-1/4" x 24-3/8" x 27-3/4" (312mm x 620mm x 705mm)	Folding:	V-fold
Acceptable Paper Weights Cassettes:	17 lb. Bond to 110 lb. Index (64gsm - 209gsm) and Transparency	Weight:	52.9 lb. (24kg)	Power Source:	From the Cassette Feeding Unit-X1 or Plain Pedestal-C1
Stack Bypass:	17 lb. Bond to 140 lb. Index (64gsm - 253gsm) and Transparency	<b>Side Paper Deck-P1 (Optional)**</b>		Dimensions (H x W x D):	42" x 26-7/8" x 24-1/4" (1,066mm x 682mm x 615mm)
Duplexing:	Standard Automatic Trayless Duplexing	Paper Deck Capacity:	2,700 Sheets (20 lb. Bond)	Weight	
Max. Mail Boxes Supported:	100	Paper Size:	Letter	Finisher-N1:	81.5 lb. (37kg)
Max. Copy Reservation:	5	Acceptable Paper Weights:	17 lb. Bond to 110 lb. Index	Finisher-N2:	125.6 lb. (57kg)
Multiple Copies:	1 to 999	Power Source:	From the Cassette Feeding Unit-X1 or Plain Pedestal-C1	<b>Copy Tray Unit-H1 (Optional)</b>	
		Dimensions (H x W x D):	17" x 12-3/4" x 23-1/4" (432mm x 324mm x 591mm)	Capacity:	100 Sheets
		Weight:	66.1 lb (30kg)	Dimensions (H x W x D):	5-1/4" x 10" x 14-5/8" (134mm x 254mm x 371mm)
				Weight:	2.2 lb (1.0kg)



## Color imageRUNNER C2620/C3220 Specifications (continued)

### Color Network Multi-PDL Printer Kit-A2 (Optional)

Type:	Embedded Print Controller
Processor:	Canon Custom Processor-Shared
RAM:	1GB
Hard Disk:	40GB-Shared
PDL Support:	UFR, PCL 5c, PostScript® 3™ Emulation, PDF 1.3
Interface Connections	
Standard:	10/100Base-T (RJ-45)
Optional:	Token Ring (Token Ring Network Interface Adaptor iN-TR2), USB Full-speed (USB Interface Board-A3) (1.1 Equivalent)
Network OS:	Novell® NetWare® v.3.2, 4.1, 4.11, 4.2, 5.0, 5.1, 6.0 (IPX/SPX™), Windows® 98/Me/2000/XP, Windows NT®, Windows Server 2003 (TCP/IP), Apple® Macintosh® OS 7.5 or Higher (DDP), Solaris™ 1.x, 2.5, or Later (TCP/IP)
Utilities:	Color Network ScanGear Remote UI™ NetSpot® Console NetSpot Job Monitor NetSpot Resource Downloader NetSpot Device Installer Canon LPR Canon NDPS Gateway Canon Font Manager 2000 EMS OpenView (C2620) EMS NetView EMS UniCenter TNG

### imagePASS-C1 V. 2.0 (Optional)

Type:	External (Back-mount) Print Controller
Processor:	Intel® Mobile Pentium® III 850MHz
RAM:	128MB Standard, 256MB Max.
Hard Disk:	20GB
PDL Support:	PCL 5c, Adobe PostScript 3
Optional Accessories:	Densitometer ED-100, Enhanced DocBuilder Pro v.2.2 (One User License)
Interface Connections	
Standard:	10/100Base-T (RJ-45)
Optional:	Parallel Port (Type B Connector) (Token Ring Board-TB84)
Network OS:	Novell NetWare v.4.1, 4.2, 5, 5.1, 6 (IPX/SPX), Windows 98/Me/2000/XP, Windows NT, Windows Server 2003 (TCP/IP), Apple Macintosh OS 7.5 or Higher (DDP), Solaris 2.5.1 or Later (TCP/IP)
Utilities:	Color Network ScanGear, Remote UI, NetSpot Console,

Canon LPR, Canon Font Manager 2000, EMS OpenView, EMS UniCenter TNG, Command WorkStation® 4.1, Command WorkStation LE 4.0 (for Mac OS), Fiery® Downloader, ColorWise® Pro Tools (Calibrator Color Editor, Profile Manager, Color Setup, Spot-On®), NetSpot Device Installer, Canon NDPS GW, Device Status Extension, EMS NetView, WebTools™, Fiery Remote Scan 5
--

### ColorPASS-Z3000† (Optional)

Type:	External Stand-Alone Controller
Processor:	Intel Pentium 4 2.4GHz
RAM:	256MB Standard, 512MB Max.
HDD:	60GB
PDL Support:	Genuine Adobe PostScript 3
Standard Interface Connection:	10/100/1000Base-T
Internal Fonts:	PS: 136 Fonts
Network OS:	Novell NetWare v.4.1, 4.2, 5, 5.1, 6, (IPX/SPX), Windows 98/Me/2000/XP, Windows NT, Windows Server 2003 (TCP/IP), Apple Macintosh OS 7.5 or Higher (DDP), Solaris 2.5.1 or Later (TCP/IP)
Utilities and Software:	Command WorkStation 4.1, Command WorkStation LE 4.0 (for Mac OSX), Fiery Remote Scan 4.x, Fiery Downloader, Fiery FreeForm, Fiery FreeForm 2, Fiery Driver (with Automatic Configurator), Secure Printing, EFI Job Monitor, ColorWise Pro Tools, E-mail port monitor, VDP Resource Manager, WebTools, Canon Color Profiles, Canon LPR, Color Network ScanGear, Device Status Extension, NDPS Gateway, NetSpot Device Installer, NetSpot Console, Remote UI

Utilities and Software:	Command WorkStation 4.1, Command WorkStation LE 4.0 (for Mac OSX), Fiery Remote Scan 4.x, Fiery Downloader, Fiery FreeForm, Fiery FreeForm 2, Fiery Driver (with Automatic Configurator), Secure Printing, EFI Job Monitor, ColorWise Pro Tools, E-mail port monitor, VDP Resource Manager, WebTools, Canon Color Profiles, Canon LPR, Color Network ScanGear, Device Status Extension, NDPS Gateway, NetSpot Device Installer, NetSpot Console, Remote UI
Optional Accessories:	Advanced Controller Interface Kit, Graphic Arts Feature Set, Enhanced DocBuilder Pro v2.2, Densitometer ED-100

### Super G3 Fax Board-M2†† (Optional)

Applicable Line:	Public Switched Telephone Network (PSTN)
Connection Lines:	1
Sending/Original Sizes:	Statement - 11" x 17"
Recording/Printing Sizes:	Statement - 11" x 17"
Transmission Times*	
ECM-MMR:	Approx. 3.2 Seconds
G3-MR:	Approx. 13 Seconds
G3-MH:	Approx. 13 Seconds
JBIG:	Approx. 2.6 Seconds

Scan Line Density	
Standard:	8 pels/mm x 3.85 lines/mm
Fine:	8 pels/mm x 7.7 lines/mm
Super Fine:	8 pels/mm x 15.4 lines/mm
Ultra Fine:	8 pels/mm x 15.4 lines/mm
Auto Dial Function	
Address Book:	1,800 Destinations (Including Destinations Stored in One-touch Buttons)
Image Memory:	Approximately 3,700 Pages (Based on ITU-T No. 1 Chart, Using Standard Settings)

### Other Optional Accessories and Utilities

Color Image Reader-C1<sup>▲▲</sup>  
 imageRUNNER Security Kit-A1P  
 imageRUNNER Copy Control Interface Cable  
 FL Cassette-X1  
 Braille Label Kit-A1  
 USB Application Interface Board-C1  
 Color Universal Send Kit-A2P for C2620<sup>††</sup>  
 Color Universal Send Kit-A2P<sup>†††</sup>  
 Universal Send PDF Encryption Kit-A1<sup>■■</sup>  
 Key Switch Unit-A1  
 Platen Cover Type G\*  
 Card Reader-D1  
 Card Sets  
 imageWARE™ Suite  
 NetSpot Suite  
 eCopy Suite  
 Canon Clustering Kit-A1<sup>▲▲</sup>

\* Either the DADF-K1 or the Platen Cover Type G is required for copy function.

\*\* Requires either the Cassette Feeding Unit-X1 or the Plain Pedestal-C1 for installation.

† ColorPASS-Z3000 is only compatible with the Color imageRUNNER C3220. Please reference the ColorPASS-Z3000 specification sheet for additional information.

†† Requires Resolution Switching Board-A2.

■ Approximate 3-second-per-page fax transmission time based on CCITT/ITU-T No. 1 Chart (JBIG, Standard Mode) at 33.6 Kbps modem speed. The Public Switched Telephone Network (PSTN) currently supports 28.8 Kbps modem speed or slower, depending on telephone line conditions.

■■ When installed on Color imageRUNNER C3220, requires system firmware upgrade 81.01 or later.

▲ Optional for Color imageRUNNER C3220 printer versions. Standard on Color imageRUNNER C2620 and Color imageRUNNER C3220 copier model.

▲▲ Requires additional hardware. Only two Color imageRUNNER C2620 or Color imageRUNNER C3220 may be clustered together.

For more information, please contact your Authorized Canon Dealer.

**Canon** KNOW HOW®

1-800-OK-CANON  
[www.usa.canon.com](http://www.usa.canon.com)

Canon U.S.A., Inc.  
One Canon Plaza  
Lake Success, NY 11042

©2005 Canon U.S.A., Inc. All rights reserved.

PostScript is a registered trademark of Adobe Systems Incorporated in the United States and/or other countries. Novell and NetWare are registered trademarks of Novell, Inc. in the United States and other countries. IPX/SPX is a trademark of Novell, Inc. Windows and Windows NT are registered trademarks of Microsoft Corporation in the United States and/or other countries. Apple and Macintosh are registered trademarks of Apple Computer, Inc. Solaris is a trademark of Sun Microsystems, Inc. in the United States and other countries. Intel and Pentium are registered trademarks of Intel Corporation. Command WorkStation, Fiery, ColorWise, and Spot-On are registered trademarks of Electronics for Imaging, Inc. in the U.S. Patent and Trademark Office and/or certain other foreign jurisdictions. WebTools, DocBuilder Pro, and Fiery FreeForm are trademarks of Electronics for Imaging, Inc. Canon, IMAGERUNNER, MEAP, NetSpot, and Canon Know How are registered trademarks, and the GENUINE logo is a trademark of Canon Inc. in the United States and may also be trademarks or registered trademarks in other countries. Remote UI is a trademark of Canon U.S.A., Inc. IMAGEANYWARE is a service mark of Canon U.S.A., Inc. in the United States. IMAGEWARE is a trademark of Canon U.S.A., Inc. in the United States and is a trademark of Canon Inc. in certain other countries. All referenced product names and other marks are trademarks of their respective owners.

All specifications are subject to change without notice.

Federal Law prohibits copying of certain documents. Violators may be subject to penalties. We suggest that you check with your own legal counsel. Canon U.S.A., Inc. and Canon Canada, Inc. intend to cooperate with Law Enforcement Agencies in connection with claims of unauthorized copying.

0605-C2620/C3220-PDF-IS

